

# CCS-UCA-MIC

## Microphone Pod



- *Attractive, low-profile design*
- *360° pickup with 20 ft (6 m) range*
- *Microphone mute button and indicator*
- *Home-run or daisy-chain wiring options*
- *12 ft (3.7 m) cable included*
- *Powered via the tabletop conference device*

The CCS-UCA-MIC is a low-profile extension microphone pod designed exclusively for use with a Crestron Flex Tabletop Conference System.<sup>1</sup> Up to two mic pods may be connected to a single conference device to extend its pickup range to cover large tables.

Optionally, two microphone pods may be daisy-chained, or connected to the mic pod ports on the rear of the conference device, using the cables provided with each microphone pod.

## Specifications

### Communications

---

A<sup>2</sup>B bus protocol, slave, synchronous data, multichannel I2S/TDM to I2S/TDM

### Audio

---

**Microphone** Triple mic array with (3) cardioid electret elements

**Pickup Range** 20 ft (6 m) typical, 360°

### Buttons & Indicators

---

**Mic Mute** (1) Capacitive button with bi-color LED, button switches between mute and unmute (affects all system mics), illuminates red when the mic is muted, illuminates green when the mic is unmuted if a USB device is connected to the conference device or a SIP call is active

### Connectors

---

**IN** (1) RJ9 4P4C connector, female;  
For connection to the conference device or to the first CCS-UCA-MIC in a daisy chain;  
12 ft (3.7 m) cable included

**OUT** (1) RJ9 4P4C connector, female;  
For connection to the second CCS-UCA-MIC in a daisy chain (not included)

### Power

---

Powered via the conference device through the A<sup>2</sup>B bus. The conference device must be powered using the [PW-2420RU](#) power pack provided with all compatible conference devices.

### Environmental

---

**Operational Temperature** 32° to 95° F (0° to 35° C)

**Storage Temperature** -4° to 160° F (-20° to 70° C)

**Humidity** 5% to 95% RH (non-condensing)

### Dimensions

---

**Height** 0.97 in (25 mm)

**Width** 3.81 in (97 mm)

**Depth** 3.42 in (87 mm)

# CCS-UCA-MIC

## Microphone Pod

### Weight

---

6 oz (170 g)

### Compliance

---

CE, IC, UL 60950-1, FCC Part 15 class B, ICES-003 Issue 6 Class B, EN 55022:2010, EN 55024:2010, IEC60950-1:2005, IEC60950-A2:2013, EN60950-1:2006, EN60950-A2:2013, CAN/CSA-C22.2

### Model

**CCS-UCA-MIC**  
Microphone Pod

#### Note:

1. CCS-UCA-MIC microphone pods are not compatible with UC-2 devices.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at [www.crestron.com/How-To-Buy/Find-a-Representative](http://www.crestron.com/How-To-Buy/Find-a-Representative) or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to [www.crestron.com/warranty](http://www.crestron.com/warranty) for full details.

The specific patents that cover Crestron products are listed online at [patents.crestron.com](http://patents.crestron.com).

Certain Crestron products contain open source software. For specific information, please visit [www.crestron.com/opensource](http://www.crestron.com/opensource).

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2020 Crestron Electronics, Inc.

Rev 09/29/20

# CCS-UCA-MIC

## Microphone Pod

