

AVerVision F17-8M

Portable FlexArm Document Camera





Visuals so life-like that students feel immersed from any seat in the classroom. Learn and discover more with F17-8M's advancing classroom visual technology.

Exceptional 8.0 Megapixel Resolution

At 30fps, zoom in and capture engaging details with F17-8M's powerful 8 megapixel sensor and 27.2x digital zoom which displays a large shooting area of 22.83" x 12.83".



Easy to Connect and Display

Present and teach with high HD quality with the convenience of HDMI or VGA input and output to your projector, monitor, or computer.



Learn From Any Angle

Create dynamic lessons with a flexible gooseneck that gives you a wide range of motion allowing your students to see details from all angles.



Create Exciting Moments

Use AVer's exclusive Sphere2 & ClassSend Software Suite to create, collaborate, upload, and share your lesson plan materials through sites such as YouTube™, Google Drive, Dropbox™.



Get America's Best Doc Cam Warranty Program

The F17-8M has the industry's only 5-year bumper-to-bumper (all-inclusive) doc cam warranty with 5-year free 2-way RMA shipping and 5-year worry-free standard advanced replacement program.





Specifications

Image

mage			
Sensor	1/3.2" CMOS	Pixel Count	8 megapixels
Effective Pixel	3840 H x 2160 V	Frame Rate	30 fps (max)
White Balance	Auto / Manual	Exposure	Auto / Manual
Image Mode	Sharp / Graphics / Motion / Microscope	Effect	Color / B/W / Negative / Mirror / Rotate / Freeze
RGB Output	1920x1080, 1280x1024, 1280x720, 1024x768, 1280x800		
Optics			
Focus	Auto / Manual	Shooting Area	Max. 22.83" x 12.83" (580mm x 326mm)
Zooming	27.2X Digital Zoom		
Function			
Image EFfect	Color / B&W / Negative / Mirror / Reverse / Freeze	White balance / exposure / night view	Auto / Manual
Picture-in-picture	Yes	Split Screen	Yes
Presentation Tools	Spotlight (Yes), Visor (Yes)	Capture Mode	Single / Continuous
Remote Control	Yes	Image Storage	240 Frames (XGA); 80 Frames (8M Pixel)
Onboard AV Recording	Yes	Onboard Annotation	No
Compatibility			
Operating Systems	Windows 7 (32/64 bit), Windows 8 (32/64 bit) Windows 10 (32/64 bit), Mac OS X 10.9 or above (Intel based), Chrome OS 29 or above	AVer Software	AVer A+ Software Suite (Sphere 2, PowerPoint Plug-in, Flash-Plug-in), Sphere Lite (for Chromebook)
Interative Whiteboard Compatibility	Yes with AVerVision Flash Plug-in *certain limitations apply		
Power			
Power Source	DC 12V, 2A, 100-240V, 50-60Hz	Consumption	12 Watts (lamp off); 12.8 Watts (lamp on)
Lighting			
Lamp Type	LED light		



Input / Output Connections

RGB Input	15-Pins D-sub (VGA)	RGB Output	15-Pins D-sub (VGA)
HDMI Input	Yes	HDMI Output	Yes
Composite Video	RCA Jack (through optional CVBS Adapter)	USB	Mini-USB 2.0 (Connect to PC), Type-A (For USB Drive)
SD	SD / SDHC (Up to 32GB)	DC 12V Input	Power Jack
MIC Input	Build in & 3.5mm jack, pink		

Dimension

Operating	16.26" x 7.68" x 17.71"	Folded	12.6" x 9.06" x 2.52"
	413mm x 195mm x 450mm		320mm x 230mm x 64mm
	(+/-2mm include rubber foot		(+/-2mm include rubber foot but
	but IR cover not included)		IR cover not included)
Weight	5.51 lbs (2.5kg)		

External Storage

Secure Digital (SDHC)	1GB ~ 32GB (FAT32)	USB Flash Drive	2GB ~ 64GB (FAT32)
-----------------------	--------------------	------------------------	--------------------

Package Contents

F17-8M	3' USB Cable (Mini type)
RGB Cable	Power Adapter 12V / 2A
Remote Control (including batteries)	Quick Guide

Optional Accessories

Microscope Adapter	Part number: VISIFSEMA	Carrying Bag	Part number: VISIOCPCC
Power Adapter	Part number: PPDC12VPA	Anti-Glare sheet	Part number: PANTIGLA1 (A5 size 8.26" x 5.84")

Others

Warranty	5 years	Advanced Replacements	During warranty period
Free 2-way RMA Shipping	Yes, during warranty period within Continental USA (including HI & AK)	Kensington Lock Option	Yes

Right Panel

Rear Panel

Left Panel



RGB in RGB out

Composite Video Output(with optional CVBS/RS232 cable)

Mini USB 2.0 port for PC

Kinsington slot

AVer Information Inc. Americas averusa.com 668 Mission Court, Fremont, CA 94539

T 408.263.3828 F 408.263.8132 toll free 1.877.528.7824