# IV-CAMPTZ-20-N-SLVR-1B

# 1 Beyond PTZ Camera, 20x Optical Zoom, NDI®|HX Compatible, Silver



A quiet, fast motor (120°/s pan speed) sets camera angles quickly.

#### Multicamera Capability with Automate Systems

Add the IV-CAMPTZ-20-N-SLVR-1B camera to an Automate multicamera system. Automate can be set to autoswitch between multiple 1 Beyond cameras to focus on the active speaking participant. Incorporate popular microphones and DSPs to switch between the presenter and audience.

#### NDI/HX Functionality

NDI|HX supports efficient and flexible IP configuration with other networked NDI-enabled devices. NDI|HX allows for easy installation and scalability with a single network pull.

#### **Mounting Options**

Standard mounting holes make it easy to mount the camera to a wall mount (included). Image flip allows the camera to be mounted inverted if needed.

- High quality video supporting resolutions up to 1080p60
- Control using VISCA over IP
- Smooth and quiet operation
- Compatible with Automate<sup>™</sup> multicamera systems
- Image Flip allows for optional inverted mounting
- Single Ethernet connection provides power (PoE+), monitoring, control, and NDI<sup>®</sup>|HX compatible video

The IV-CAMPTZ-20-N-SLVR-1B<sup>1</sup> is a high quality PTZ IP camera that can output up to 1080p60 resolution video via the 3G-SDI or HDMI® ports. It is ideal for any meeting where one camera needs to capture several areas of the room. Combine with 1 Beyond Automate VX for a multi-camera speaker (presenter) tracking solution. The IV-CAMPTZ-20-N-SLVR-1B camera supports a single Ethernet connection and provides power (PoE+), monitoring, control, and NDI® JHX video.

#### **High Quality Video**

A high quality Sony Exmor® CMOS sensor enables the camera to output up to 1080p60 resolution video via the 3G-SDI or HDMI ports.

## **Manual Control Options**

Use VISCA over IP to control the camera with a Crestron® control system. 1B Cam Manager Software is included for easy configuration from a computer on the network.

## Quiet, Fast Switching Between Presets

Up to 256 pan, tilt, and zoom combination presets can be configured. The camera will move to the selected preset point.



# IV-CAMPTZ-20-N-SLVR-1B

# 1 Beyond PTZ Camera, 20x Optical Zoom, NDI® | HX Compatible, Silver

# **Specifications**

# **Optics and Processing**

Image Sensor	1/2.8 in. Sony Exmor CMOS, 2.14MP
Focal Lens & Iris	f=4.7-94 mm, F1.6 - F3.5
Field of View	59.5° - 2.9°
Focus System	Auto, Manual, PTZ Trigger, One Push
Minimum Illumination	0.5 Lux (30FPS)
Shutter Speed	1/1 - 1/10,000 sec
Gain	Auto, Manual
White Balance	Auto, Indoor, Outdoor, One Push, Manual
Exposure	Auto, Manual, Shutter Priority, Iris Priority
Number of Presets	Up to 256
Serial Control	RS-485, RS-232 (VISCA, PELCO-D)
IP Control Protocol	HTTP, RTP, TCP, UDP, ONVIF

# Pan, Tilt, Zoom

Tilt/Pan Angle	Tilt: 30° - 90°, Pan: 170° - 170°
Tilt/Pan Speed	Tilt: 0.1° - 90° /s, Pan: 0.1° - 120° /s
Zoom	20x Optical, 20x Digital

# Connectivity

Ethernet

RJ-45, 100Mb

## Video

Video Outputs <sup>1</sup>	3G-SDI, HDMI, NDI HX over Ethernet <sup>2</sup>
Signal Formats (HD)	1080p60/50/30/25, 1080i60/50, 720p60/50/30/25
IP Video Compression	H.264 (Dual stream)
Streaming	RTSP, RTMP
Streaming Resolution	Up to 1080p30, User-selectable framesize/framerate/bitrate

## Audio

IP Audio	AAC
Compression	
Audio Input	1x Line In

## Power

Power 12VDC, <30 W, PoE+ **PoE+ Rating** 25.5 W

NOTE: To comply with the European Directive (CE), shielded CAT5e cable must be used as a minimum for PoE power.

## Environmental

Temperature	32° to 104°F (0° to 40°C)
-------------	---------------------------

#### Construction

Mounting	1/4 in. threaded mount hole, compatible with Wall Mount and J-Mount ceiling bracket
Color	Silver
S/N	≥50dB

8.9 in. x 8.1 in. x 6.3 in. (226 mm × 206 mm ×

## **Dimensions**

Dimensions

```
160 mm)
```

# Weight

3.74 lb (1.7 kg)

Note:

1. The IV-CAMPTZ-20-N-SLVR-1B camera includes integrated circuits produced by HiSilicon (part numbers HI3516ARBCV100 and HI3516ARFCV200), a subsidiary of Huawei Technologies Company.

# Included Accessories

**Power Supply** 

Wall Mount

Serial Control Breakout

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or by calling 855-263-8754.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics. Inc. in the United States and/or other countries. HDMI is either a trademark or a registered trademark of HDMI Licensing LLC in the United States and/or other countries. NDI is either a trademark or a registered trademark of NewTek, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their





# IV-CAMPTZ-20-N-SLVR-1B

# 1 Beyond PTZ Camera, 20x Optical Zoom, NDI®|HX Compatible, Silver

products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

# HDMI

Crestron and the Crestron logo are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Wirecast is either a trademark or a registered trademark of Telestream, LLC in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 08/19/22

