### Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams® Software



- Native Microsoft Teams® touch screen UX with simple operation and one-touch meeting joins
- Supports Teams® display upgrade
- Built-in camera for HD video calling
- Dedicated Microsoft Teams button
- Wideband HD voice quality
- Hearing aid compatible handset
- Wired or Bluetooth® enabled headset support
- Easy to specify and install no custom design, programming, or software installation required
- Enterprise-grade security connects and communicates securely over any enterprise or SMB network
- Network management and provisioning and system alerts through the XiO Cloud<sup>®</sup> service

The Crestron Flex UC-P10-T-C-HS desk phone provides a premium video collaboration solution for use with the Microsoft Teams intelligent communications platform. It offers Full HD quality video and audio calling, capability to view and zoom the shared content, and full-duplex hands-free speakerphone capability in an elegant desktop design. It features a large 10 in. color touch screen display, built-in Full HD camera with privacy shutter, hearing aid compatible handset, and wired or Bluetooth® enabled headset support.<sup>1,2</sup> Each phone can be synced with a Microsoft Teams account, with contacts, schedules, voicemails, and other preference settings appearing on the phone's touch screen.

### Native Microsoft Teams® Rooms Experience

The UC-P10-T-C-HS desk phone provides a native Microsoft Teams IC software experience, with simple operation and onetouch meeting joins through a feature-rich touch screen. Onboard calendar, corporate directory access, and hot desking are provided. The UC-P10-T-C-HS works with a Microsoft Teams account and connects to an enterprise or SMB network implementing a cloud based Microsoft Teams deployment.

### Supports Microsoft Teams® Display Upgrade

The UC-P10-T-C-HS Microsoft Teams desk phone can be upgraded to Microsoft Teams display<sup>3</sup>.

In addition to Microsoft Teams supported features, Microsoft Teams display offers unique features such as:

- Dedicated displays for Teams allow users to access all core Teams features.
- **Ambient personalizable display** allows users to see important activities and notifications without context-switching on their primary work device.
- Leave a note on lock screen allows users to check audio, video, and text notes left by guests.

To learn more, see Microsoft Teams displays.

### NOTES:

- The UC-P10-T-C-HS desk phone cannot be reverted to a Microsoft Teams phone once upgraded to Microsoft Teams display.
- The handset and capacitive Microsoft Teams button are not supported by Microsoft Teams display software. Remove the handset after upgrading the desk phone to Microsoft Teams display.

### Intuitive User Interface

The large 10 in. HD touch screen makes the desk phone easy to use. The capacitive buttons provide the essential controls for managing a call in progress, muting or adjusting volume, switching to hands-free or headset mode<sup>1</sup>, and a dedicated Teams button to launch the home screen or calls app. The intuitive touch screen UI employs a look and layout similar to Microsoft Teams and Office 365° software, so users can move effortlessly between using a phone and personal computer at their desk and other Microsoft Teams based Crestron UC conferencing solutions in a meeting room.

### High-Definition Video Conferencing

The built-in camera with a wide-angle 96° diagonal field of view, Full HD 1080p video resolution, 2 MP CMOS sensor, and advanced video processing ensures a clear video image free from light or noise artifacts.



## Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams® Software

### **High-Definition Audio Conferencing**

The UC-P10-T-C-HS desk phone facilitates conversations with highly intelligible voice clarity, whether speaking privately on the handset or a headset<sup>1</sup>, or conferencing using the hands-free speakerphone function. High-performance AEC technology achieves transparent full-duplex performance free of distracting echo or noise. Wideband audio codec support allows for full-spectrum, bidirectional voice communication. The handset is hearing aid compatible to ensure an optimal experience for individuals with hearing impairment.

### Hot Desking

For organizations employing shared workstations or offices, workers can log in at any UC-P10-T-C-HS desk phone using their personal Microsoft Teams account. Once signed in, the individual's presence status, contacts, voicemail, and meeting schedule immediately sync with their account for a seamless user experience.

### **Enterprise-Grade Security**

Crestron Flex is an enterprise-grade solution, engineered in partnership with Microsoft to integrate seamlessly into any Microsoft Teams Rooms software deployment. Crestron Flex is ideally equipped for mass deployment throughout any sized facility.

### Easy Provisioning and Device Management

The XiO Cloud service is an IoT cloud based provisioning service that enables installers and IT managers to easily deploy and manage thousands of devices.

Visit www.crestron.com/xiocloud for additional information.

### **Specifications**

### **Included Components**

UC-P10-T-C-HS	Crestron Flex 10 in. Video Desk Phone with handset for Microsoft Teams® Software:		
	<ul> <li>Cable, CAT5e, RJ45-to-RJ45, approx. 12 ft (3.7 m)</li> </ul>		
	<ul> <li>HD wideband handset</li> </ul>		
	<ul> <li>Cable, handset, RJ9-to-RJ9, approx. 11.5 ft (3.5 m)</li> </ul>		

### Communications

Ethernet	Dual 10/100/1000 Mbps, auto-switching, auto-negotiating, auto-discovery, full/half duplex, DHCP, TCP/IP, UDP/IP, CIP, SSL, TLS, SSH, SFTP (SSH File Transfer Protocol), SRTP, IEEE 802.1X, Active Directory® authentication, digest access authentication, password login, XiO Cloud client, Microsoft Intune® client, IEEE 802.3at Type 2 PoE+ compliant
VoIP	Microsoft Teams client; compatible with Office 365 cloud service; supports Enterprise Voice, Phone System, Office 365 modern authentication (limited), directory lookup, PSTN calling, E911, common area phone, calendar, hot desking; DTMF tone generation (RFC 2833 out-of-band, in-band), acoustic echo cancellation, automatic gain control, voice activity detection, comfort noise generator, low-delay audio packet transmission, adaptive jitter buffers, packet loss concealment
Wi-Fi <sup>®</sup>	Dual-band 802.11a/b/g/n/ac (2.4 GHz & 5 GHz)
Bluetooth®	Bluetooth V5.0 BR+EDR+BLE
USB	USB 3.0
Camera	
Image Sensor	2 Megapixel CMOS sensor
Resolution/FPS	HD 1080p @ 30 fps
Field of View	96° diagonal, 88° horizontal, 57° vertical

Yes



# Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams® Software

ALC       Automate Gain Control, Dynamic Noise Reduction, Acoustic Echo cancellation, Full-duplex [EE 1329 Type 1 compliant <ul> <li>Flashes green to indicate Boot up</li> <li>Built-in 21'S digital MEMS microphones, comi-directional microphones, 360- degree of audio pickup</li> </ul> Flashes green to indicate Boot up <ul> <li>Blinks red to indicate Boot up</li> <li>Blinks red to indicate Bluetooth</li> <li>headset paired</li> <li>Solid blue to indicate Bluetooth</li> <li>headset paired</li> <li>Off to indicate idle</li> </ul> PIR Detection Range       Approx. 6.5 ft (2 m) in front of touch screen, wakes touch screen and display device <ul> <li>Outrols brightness of the touch screen</li> <li>Solid blue to indicate idle</li> <li>Hook Switch</li> <li>Connectors</li> </ul> Display Type       TFT active matrix color LCD       Internet <ul> <li>B-pin RJ45 connector, female;</li> <li>Toouch Screen</li> <li>Copacitive, multi-touch capable</li> <li>Language</li> <li>Sopport</li> <li>Tradicional Chinese (2H-TW), Cacch (CS), Danish (DA), Dutch (NL), English (UK),</li></ul>	Audio		Light Bar (Status LED)	(1) Light Bar (below touch screen) illuminates different colors to indicate the
Microphones       Built-in 2 IS digital MEMS microphones, 300- degree of audio pickup       Flashes yellow intermittently to indicate voicemail         Speaker       Full range speaker; Amplifier Power: 2 Watts (rated power); Output Volume: 87 ± 3 dBA       - Flashes yellow intermittently to indicate voicemail         Handset       HD wideband handset, hearing aid compatible (HAC)       - Solid red indicate shore is muted, solid red indicate shore is muted, off to indicate shore is muted, solid red is muter is muted, solid red is muter is	AEC	Reduction, Acoustic Echo cancellation,		5
Speaker       Amplifier Power: 2Watts (rated power); Output Volume: 87 ± 3 dBA       solid green indicates call is in progress         Handset       HD wideband handset, hearing aid compatible (HAC)       Solid blue to indicate Bluetooth headset paired         Occupancy Sensor       Approx. 6.5 ft (2 m) in front of touch screen, wakes touch screen and display device       Off to indicate idle         PIR Detection Range       Approx. 6.5 ft (2 m) in front of touch screen, wakes touch screen and display device       Controls brightness of the touch screen         Display Type       TFT active matrix color LCD Display Type       TFT active matrix color LCD Size       Internet       (1) 8-pin RJ45 connector, female; 1000Base-T Ethernet port; Switched LAN port for optional computer connection         Touch Screen       Capacitive, multi-touch capable Language       Internet       (1) 8-pin RJ45 connector, female; 1000Base-T Ethernet port; Switched LAN port for optional computer connection to LAN with PoE PSE         Support       Traditional Chinese (2H-TW), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (PE), Soreu (EL), Hebrew (HE), Hungarian (HU), Ktolin (TT), Japanese (JP), Nortuguese - Portzigl (PT-PP), Portuguese - Portzigl (PT-PP), Portuguese - Parzigl (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)         Buttons & Indicates       (6) Capacitive buttons for Teams, Volume -/r., Headset*, Mute*, Speakerphone*, *Buttons are LED backlit to indicate active status       32 <sup>n</sup> to 104 <sup>o</sup> F (O <sup>o</sup> to 40 <sup>o</sup> C) +Umidity         Constru	Microphones	omni-directional microphones, 360-		<ul> <li>Flashes yellow intermittently to indicate voicemail</li> </ul>
Handset       HD wideband handset, hearing did compatible (HAC)       Solid blue to indicate Bluetooth headset paired         Occupancy Sensor       - Off to indicate idle         PIR Detection Range       Approx. 6.5 ft (2 m) in front of touch screen, wakes touch screen and display device       - Off to indicate idle         Ambient Light Sensor       Controls brightness of the touch screen       - Off to indicate idle         Touch Screen       Controls brightness of the touch screen       - Off to indicate idle         Display Type       TFT active matrix color LCD       - Off to indicate paired         Size       10 in. (254 mm) diagonal       - Off to applicate parts PoE D part; Touch Screen         Language       Arabic (AR), Simplified Chinese (ZH-CN), Traditional Chinese (ZH-TW), Czech (CS), Danish (PA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Portugal (PT-BR), Romaina (RO), Russian (RU), Slowak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Environmental         Button	Speaker	Amplifier Power: 2 Watts (rated power);		<ul><li>solid green indicates call is in progress</li><li>Blinks blue to indicate Bluetooth</li></ul>
PIR Detection Range       Approx. 6.5 ft (2 m) in front of touch screen, wakes touch screen and display device         Ambient Light Sensor       Controls brightness of the touch screen         Touch Screen       Controls brightness of the touch screen         Display Type       TFT active matrix color LCD         Size       10 in. (254 mm) diagonal         Resolution       1280 x 800 pixels         Touch Screen       Capacitive, multi-touch capable         Language       Arabie (AR), Simplified Chinese (ZH-CN), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (F), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Itolian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Portugal (PT- PT), Portuguese - Protugal (PT- PT), Portuguese - Protugal (PT- PT), Nortuguese - Pr	Handset			Solid blue to indicate Bluetooth
Range       screen, wakes touch screen and display device         Ambient Light Sensor       Controls brightness of the touch screen         Display Type       TFT active matrix color LCD         Display Type       TFT active matrix color LCD         Size       10 in. (254 mm) diagonal         Resolution       1280 x 800 pixels         Touch Screen       Capacitive, multi-touch capable         Language       Arabic (AR), Simplified Chinese (ZH-CN), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Fortugal (PT-PT), Rustion (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power over Class 4 PoE+ powered device*         Buttons & Indicators       Environmental         Gagacitive buttons for Teams, Volume twith using       20° to 104°F (0° to 40°C)         Wattoms       (6) Capacitive buttons for Teams, Volume active status       Environmental         Temperature active status       20° to 104°F (0° to 40°C)       Humidity         Buttons       (6) Capacitive buttons for Teams, Volume active status       Metal and plastic, fixed-angle touch screen	Occupancy Sensor			Off to indicate idle
Ambient Light Sensor       Controls brightness of the touch screen         Touch Screen       Controls brightness of the touch screen         Display Type       TFT active matrix color LCD         Size       10 in. (254 mm) diagonal         Resolution       1280 x 800 pixels         Touch Screen       Capacitive, multi-touch capable         Language       Arabic (AR), Simplified Chinese (ZH-CN), Support       Internet       (1) 8-pin RJ45 connector, female; 1000Base-T Ethernet port & PoF PD port; For connection to LAN with PoE PSE         Uanguage       Arabic (AR), Simplified Chinese (ZH-CN), Support       Internet       (1) RJ9 4PAC connector, female; For handset         Headset       (1) RJ9 4PAC connector, female; For handset       Headset       (1) USB-C® connector, female; For handset         Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norweign (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power Power over       Class 4 PoE+ powered device* *POE injector available separately         Buttons & Indicators       Environmental       Temperature active status       32° to 104°F (0° to 40°C)         Humidity       10% to 90% RH (non-condensing)       Construction         Buttons       Metal and plastic, fixed-angle touch screen       Metal and plastic, fixed-angle touch	PIR Detection         Approx. 6.5 ft (2 m) in front of touch		Hook Switch	(1) Magnetic handset hook switch
Sensor       Touch Screen         Display Type       TFT active matrix color LCD         Size       10 in. (254 mm) diagonal         Resolution       1280 x 800 pixels         Touch Screen       Capacitive, multi-touch capable         Language       Arabic (AR), Simplified Chinese (ZH-CN), Danish (DA), Dutch (NL), English (US), English (US), Finnish (FI), French (FR), German (DE), Creek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Portugal (	•	device	Connectors	
Touch Screen       connection         Display Type       TFT active matrix color LCD         Size       10 in. (254 mm) diagonal         Resolution       1280 x 800 pixels         Touch Screen       Capacitive, multi-touch capable         Language       Arabic (AR), Simplified Chinese (ZH-CN), Support         Traditional Chinese (ZH-TW), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Partugal (PT- PT), Portuguese - Portugal (PT- PT), Portuguese - Stazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)         Buttons & Indicators       Class 4 PoE+ powered device* *POE injector available separately Power         Capacitive       (6) Capacitive buttons for Teams, Volume active status       Environmental         Temperature active status       32° to 104°F (0° to 40°C)         Humidity       10% to 90% RH (non-condensing)	Sensor	Controls brightness of the touch screen	PC	1000Base-T Ethernet port;
Size       10 in. (254 mm) diagonal       1000Base-T Ethernet port & PoE PD port; For connection to LAN with PoE PSE         Resolution       1280 x 800 pixels       (1) RJ9 4P4C connector, female; For handset         Touch Screen       Capacitive, multi-touch capable       Handset       (1) USB-C® connector*, female; For headset (not included)         Language       Arabic (AR), Simplified Chinese (ZH-CN), Traditional Chinese (ZH-TW), Czech (CS), Danish (DS), Finnish (F), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power       Class 4 PoE+ powered device*         Buttons & Indicators       Environmental       Temperature Active status       -17 W         Capacitive buttons       (6) Capacitive buttons for Teams, Volume active status       Environmental         Temperature active status       32° to 104°F (0° to 40°C)       Humidity         Housing       Metal and plastic, fixed-angle touch screen	Touch Screen			connection
Resolution       1280 x 800 pixels         Touch Screen       Capacitive, multi-touch capable         Language       Arabic (AR), Simplified Chinese (ZH-CN), Traditional Chinese (ZH-TW), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power         Buttons & Indicators       Capacitive buttons       (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       Environmental         Temperature Buttons       32° to 104°F (0° to 40°C) Humidity       10% to 90% RH (non-condensing)         Construction       Metal and plastic, fixed-angle touch screen	Display Type Size		Internet	1000Base-T Ethernet port & PoE PD port;
Touch ScreenCapacitive, multi-touch capablehandsetLanguage SupportArabic (AR), Simplified Chinese (ZH-CN), Traditional Chinese (ZH-TW), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)Headset(1) USB-C® connector*, female; For headset (not included) * Backward compatible with USB-A peripherals via USB-C to USB-A adaptor (not included)Buttons & IndicatorsClass 4 PoE+ powered device* * POE injector available separately Power ConsumptionPowerCapacitive buttons(6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active statusEnvironmentalTemperature active status32° to 104°F (0° to 40°C) 10% to 90% RH (non-condensing)ConstructionHousingMetal and plastic, fixed-angle touch screen	Resolution	1280 x 800 pixels	l lan de et	
Support       Traditional Chinese (ZH-TW), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese (JP), Korean (KO), Norwegian (NO), Polish (PL), Portuguese - Portugal (PT- PT), Portuguese - Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power         Buttons & Indicators       Class 4 Indicators         Capacitive buttons       (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       Environmental         Construction       Temperature Humidity       32° to 104°F (0° to 40°C) Humidity         Humidity       10% to 90% RH (non-condensing)         Construction       Humidity         Mutal and plastic, fixed-angle touch screen	Touch Screen	Capacitive, multi-touch capable	Hanaset	
Polish (PL), Portuguese - Portugal (PT-PT), Portuguese - Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power over Ethernet       Class 4 PoE + powered device* *POE injector available separately         Buttons & Indicators       Power (TH)       ~ 17 W         Buttons & Indicators       Environmental         Capacitive buttons       (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       Environmental         Temperature active status       32° to 104°F (0° to 40°C)         Humidity       10% to 90% RH (non-condensing)         Construction       Housing         Metal and plastic, fixed-angle touch screen		Traditional Chinese (ZH-TW), Czech (CS), Danish (DA), Dutch (NL), English (UK), English (US), Finnish (FI), French (FR), German (DE), Greek (EL), Hebrew (HE), Hungarian (HU), Italian (IT), Japanese	Headset	headset (not included) *Backward compatible with USB-A peripherals via USB-C to USB-A adaptor
PT), Portuguese -Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak (SK), Spanish (ES), Swedish (SV), Thai (TH)       Power over Ethernet       Class 4 PoE+ powered device* *POE injector available separately         Buttons & Indicators       Power (TH)       ~17 W         Capacitive buttons       (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       Environmental         Temperature active status       32° to 104°F (0° to 40°C) 10% to 90% RH (non-condensing)         Construction       Housing       Metal and plastic, fixed-angle touch screen		Polish (PL), Portuguese - Portugal (PT- PT), Portuguese -Brazil (PT-BR), Romanian (RO), Russian (RU), Slovak	Power	
(TH) Buttons & Indicators Capacitive buttons (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status (7) W Consumption (7) W Constructed (7) W Construction (				*POE injector available separately
Capacitive buttons       (6) Capacitive buttons for Teams, Volume -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       32° to 104°F (0° to 40°C)         Humidity       10% to 90% RH (non-condensing)         Construction         Housing       Metal and plastic, fixed-angle touch screen		(TH)		~ 17 W
buttons       -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       Humidity       10% to 90% RH (non-condensing)         Construction       Housing       Metal and plastic, fixed-angle touch screen	Buttons & India	cators	Environmental	
buttons       -/+, Headset*, Mute*, Speakerphone*; *Buttons are LED backlit to indicate active status       Humidity       10% to 90% RH (non-condensing)         Construction       Housing       Metal and plastic, fixed-angle touch screen	Capacitive buttons		Temperature	32° to 104°F (0° to 40°C)
Construction       Housing     Metal and plastic, fixed-angle touch screen		*Buttons are LED backlit to indicate	Humidity	
screen			Construction	
Mounting Surface mount, wall mount (optional)			Housing	
			Mounting	Surface mount, wall mount (optional)



## Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams® Software

### **Dimensions**

Height	8.66 in. (220 mm)
Width	12.91 in. (328 mm)
Depth	4.96 in. (126 mm)

### Weight

5.10 lb (2.30 kg)

### Compliance

FCC Part 15 class B, ICES-003 Issue 6 Class B, EN 55032, EN55035 / EN61000-4

### Regulatory Model: M202029001

### Models

### UC-P10-T-C-HS

Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams® Software

### UC-P10-T-C-HS-I

Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams Software, International

### Available Accessories

For a list of available accessories, visit the UC-P10-T-C-HS product page.

#### Notes:

- 1. The headset is not included. Visit https://www.microsoft.com/enus/microsoft-365/microsoft-teams/across-devices/devices/ for recommended accessories.
- 2. Only one headset, either wired or Bluetooth-enabled, is supported at a time.
- 3. To upgrade the UC-P10-T-C-HS Microsoft Teams phone to Teams Display, refer to its product manual.

This product may be purchased from select authorized Crestron dealers and distributors. To find a dealer or distributor, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/How-To-Buy/Find-a-Representative or contact us for additional information by visiting https://www.crestron.com/contact/ourlocations for your local contact.

This product is covered under the Crestron standard limited warranty. Refer to www.crestron.com/warranty for full details.

The specific patents that cover Crestron products are listed online at patents.crestron.com.

Certain Crestron products contain open source software. For specific information, please visit www.crestron.com/opensource.

Crestron, the Crestron logo, and XiO Cloud are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Bluetooth is either a trademark or reaistered trademark of Bluetooth SIG. Inc. in the United States and/or other countries. Active Directory. Microsoft, Microsoft Intune, Microsoft Teams, and Office 365 are either trademarks or registered trademarks of Microsoft Corporation in the United States and/or other countries. USB-C is either a trademark or registered trademark of USB Implementers Forum, Inc. in the United States and/or other countries. Wi-Fi is either a trademark or registered trademark of Wi-Fi Alliance in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography.

Specifications are subject to change without notice.

©2022 Crestron Electronics, Inc.

Rev 10/28/22



# Crestron Flex 10 in. Video Desk Phone with Handset for Microsoft Teams® Software

UC-P10-T-C-HS



